COMMERCIAL FRONT END LOADER



DESCRIPTION

PRODUCT DESCRIPTION

Commercial Model

1200 KG Lifting Capacity

Installation on independent hydraulic output.

Lifting Capacity up to 1200 KG

Installation of PTO Gearbox + 9 Plunger Pump

Improves pressure and lifting capacity

Removes limitation of continuous use

Independent oil tank - capacity 80 liters

Counter weight box (optional)

Heavy duty hydraulic rams

Conversion of front rims, hubs and bearings

Replaceable earth digging teeth

SPECIFICATIONS

Model Commercial

Bucket Size 60 ~66

Lifting Height 132 ~144

Cylinder 4(Bore 80mm x Rod 50mm)

Control Valve 60 ltr 2 Spool Valve

Hose Pipe 6000 PSI Double Breaded

Sleeve Steel Tube Honed

Rod Hard Chromed Carbon Steel

Seal V Type

Pump PTO Gear or Piston

Oil Tank 90 Liter Oil With Section Line filter

Weight Box 36 x 36 x32 (optional)

Oil Gauge and Breather Available

Maximum Flow 35-40 Litters

Operating Pressure 2250 PSI

Front Rim Hub & Tire Conversions to 8.25 x 16





8KM Sheikhupura Road, Opp. Millat Tractors Limited, Lahore, Pakistan





