

# DISC PLOUGH

PRIMARY TILLAGE –  
SOIL PREPARATION IMPLEMENTS

PERFORMS SOIL TURNING,  
SOIL BREAKING AND SOIL RAISING.



**MADFI**

# DESCRIPTION

## FEATURES

Deep Ploughing in root-infested, sticky, stony and hard soils.

Turns the furrow slice to one side in 'Scooping Action'

Mixes remains of crops and weeds throughout the depth of ploughing.

Ideal for rain-fed areas for checking soil erosion by water and wind.

Also works very well in stone free lands.

Follow-up with secondary tillage (harrowing) not necessary as compares to Mould Board Plough.

Handles obstacles much easily.

Requires less power.

## SPECIFICATIONS

Disc Size	660 mm	660 mm	660 mm	660 mm
Furrow Width	254 mm	254 mm	254 mm	254 mm
Maximum Working Depth	300 mm	300 mm	300 mm	300 mm
Vertical Disc Adjustment	15/18/22	15/18/22	15/18/22	15/18/22
Clearance	522 mm	522 mm	522 mm	522 mm
Weight	280 kg	330 kg	410 kg	485 kg
Attachment	Cat II	Cat II	Cat II	Cat II
Power Req.	35-45HP	50-65HP	70-90HP	95-110HP
Bearings	Tapper Roller	Tapper Roller	Tapper Roller	Tapper Roller
Furrow Wheel Dia	508 mm	508 mm	508 mm	508 mm



8KM Sheikhpura Road,  
Opp. Millat Tractors Limited,  
Lahore, Pakistan



Tel:+92-42-37925318, 37925218  
Fax: +92-42-379299371



madfi786@yahoo.com



www.madfi.com.pk