

TRACTOR BACKHOE

SUITABLE FOR DIGGING
TRENCHES, EXCAVATING,
LANDSCAPING

AVAILABLE IN 3 SIZES



MADFI

DESCRIPTION

Tractor Mounted Backhoe.

Suitable for trenching, landscaping & excavating.

PTO driven, attached in independent hydraulic system.

Quick Attachment.

Replaceable bucket teeth.

Available in 3 different sizes.

SPECIFICATIONS

3 point Linkage	1 & 2	1 & 2	2 & 3
Maximum digging depth (A)	92.6	116	146
Digging depth (two foot flat bottom)	72	106	134
Reach from swing pivot (B)	122.6	159	196
Boom height from ground (C)	118	132	188
Transport height (D)	88	102	132
Bucket Size	16x 18	16 x 18	18 x 24
Bucket rotation	165 degree	165 degree	170 degree
Swing arc	145 degree	145 degree	145 degree
Stabilize spread down (Operating)	90	96	96
Stabilize spread up (Transporting)	60	66	66
Lift at end of boom	760 lbs.	820 lbs.	930 lbs.
Hydraulic Pressure	2250 PSI	2250 PSI	2250 PSI
Hydraulic flow requirements minimum	4.5~6 GPM	4.5~6 GPM	4.5~8 GPM
Minimum Tractor HP	40~48 Hp	60~80 Hp	80~110 Hp
All Boom & Bucket cylinder Bore	75~80 mm	75~80 mm	75~80mm
All Boom & Bucket Rod	50 mm	50 mm	50 mm



8KM Shekhupura Road,
Opp. Millat Tractors Limited,
Lahore, Pakistan



madfi786@yahoo.com



Tel: +92-42-37925318, 37925218
Fax: +92-42-379299371



www.madfi.com.pk